

**MID AMERICA**



**MOTORWORKS**

Pursue your passion here

---

## **Suggested Installation Instructions for 100-958 Metal Arrester Oil Filter Magnet**

To install your new Metal Arrester on your car simply take the unit out of the package and push it on to the end of your oil filter. There are no tools required to install the Metal Arrester on your car. The unit will fit on the filter with up to a 1/8" side clearance, which is normal. The space-age magnet will hold the unit in place. If you prefer not to install the unit yourself simply take it with you the next time you have the oil changed and have the shop put it on for you. We thank you for your purchase and your car will thank you for years to come.

### **LIMITED WARRANTY**

All Metal Arresters are warranted to the original retail purchaser to be free from defects in material and workmanship for lifetime. Authorized Metal Arrester dealers do not have authority to make any warranties in addition to or inconsistent with the terms or conditions set forth in this warranty. All transportation charges must be paid for by purchaser.

The Metal Arrester was designed to fit premium made filters such as FRAM, AC DELCO, MOTORCRAFT, and PUROLATOR. In some isolated cases the unit maybe too small for a particular non-brand name filter. In the event the unit is too small we suggest that the next time you change your oil purchase one of the filters listed above.

24 HOUR CUSTOMER SERVICE # 1-800-235-MOTOR