



Pursue your passion here

P.O. Box 1368 • Effingham, IL 62401 • Worldwide: 217-540-4200 • FAX: 217-540-4800  
 Call Toll-Free U.S. & Canada 800-500-1500 • Web: www.mamotorworks.com • E-mail: mail@mamotorworks.com

## Suggested Installation Instructions for: 106-131 Flexible Bonding Clear

*PROMOTES ADHESION ON HARD PLASTICS, POLYETHYLENE, POLYPROPYLENE, & THERMO PLASTIC OLEFIN*

**DANGER! EXTREMELY FLAMMABLE! CONTENTS UNDER PRESSURE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. KEEP AWAY FROM CHILDREN. IRRITANT TO EYES, SKIN AND RESPIRATORY TRACT. READ HEALTH HAZARD INFORMATION BELOW.**

*Performance Choice Flexible Bonding Clear is designed to promote adhesion of top coat materials when repairing or refinishing hard plastics such as polyethylene, polypropylene, & thermo plastic olefin. Flexible Bonding Clear works equally well on all flexible or rigid plastics.*

The identification of plastics has always been a major concern. Now, however with the advent of FLEXIBLE BONDING CLEAR and its superior bonding characteristics, this is no longer a problem.

### DIRECTIONS FOR USE

1. For best results, wash area with soap and water. Next clean thoroughly with Performance Choice PLASTIC PREP.
2. For best results, use only when can temperature is above 60 degrees F.
3. SHAKE CAN vigorously for at least one minute after mixing ball rattles.
4. Hold can upright approximately 12 inches from surface during application. Use steady even strokes while spraying.
5. Apply light "mist" coats. For best results, apply coats in 5 to 10 minute intervals. Several thin coats are better than one heavy coat. Allow 10-15 minutes to dry, but NO MORE THAN 30 MINUTES BEFORE TOPCOATING.
6. If clogging develops, remove spray button with a twisting motion and clean with lacquer thinner. Do not stick objects into can opening.
7. After each use, turn can upside down and spray several seconds to clear spray button.
8. Discard empty can in trash pick-up. DO NOT incinerate or compact.

**CONTAINS: TOLUENE, PETROLEUM DISTILLATES, ISOBUTANE, PROPANE**

**DANGER! EXTREMELY FLAMMABLE.** Do not spray near sparks, heat or open flames. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. **DO NOT SMOKE** - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools, and appliances, and any other sources of ignition. **CONTENTS UNDER PRESSURE.** Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water, and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120 degrees F. Do not discard empty can in home garbage compactor. **VAPOR HARMFUL.** Use with adequate ventilation. Avoid continuous breathing of vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **HARMFUL OR FATAL IF SWALLOWED.** If swallowed do not induce vomiting. Call physician immediately.

**INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.**

### **DANGER: HARMFUL/FLAMMABLE**

- \* Keep away from heat, sparks & flame
- \* Do not inhale vapors or mist
- \* Harmful if absorbed through the skin
- \* Avoid contact with eyes & skin
- \* Do not swallow

### **PRECAUTIONS:**

- \* Wear chemical goggles & resistant gloves
- \* Keep container tightly closed
- \* Wash thoroughly after handling

### **FIRST AID:**

- \* In case of contact, flush eyes & skin with water for 15 minutes
- \* If swallowed, do not induce vomiting
- \* Call your nearest emergency room or poison control center